

Technical Request

1. The appearance and surface of the product should be clean, without rust spots, mildew, scratches, No obvious burr and other surface defects.
2. Shell riveted firmly, no obvious gap, size in line with the drawing requirements.
3. Make the impeller ø60, diagonal flow,28 blades, steel shaft ø3, bushing ø 1.5
4. Safety performance in accordance with GB/T13933-2008 regulations.
5. Unnoted tolerance is GB/T1804-v.

No.	Item	Material	Qty
1	Motor		1
2	Right Side Plate	Iron	1
3	Air Outlet Plate	Al	1
4	Air Inlet Plate	Al	1
5	Impeller	Al	1
6	Left Side Plate	Iron	1

SPECIFICATION

VOLTAGE (V)	24
CURRENT (A)	0.42±10%
SPEED (r/min)	2000±150
AIR VOLUME (m^3/h)	203
BEARINGS	Ball bearing
SPEED CONTROL	0~10V

Mark	Qty	Sign	Name	Date

Stage Mark	S		
Version	A1	Name	Date
Design		JIN	20250618
Audit			
Technical			
Standard			
Approve			

Material | Ratio 1:1 | Weight

Ningbo Longwell Electric Technology Co., Limited

LWCD-60240MN-07

第 1 页 共 1 页