



1. The appearance and surface of the product should be clean, without rust spots, mildew, scratches, No obvious burr and other surface defects.
2. Shell riveted firmly, no obvious gap, size in line with the drawing requirements.
3. Make the impeller $\phi 30, 20$ blades, steel shaft $\phi 3$, bushing $\phi 1.5$
4. Safety performance in accordance with GB/T13933-2008 regulations.
5. Unnoted tolerance is GB/T1804-v.

SPECIFICATION	
VOLTAGE (V)	12
CURRENT (A)	/
SPEED (r/min)	1400±10%
AIR VOLUME (m ³ /h)	/
BEARINGS	Ball bearing
SPEED CONTROL	/

7								
6		Left Side Plate	1	Iron				
5		Impeller	1	Aluminium				
4		Air Outlet Plate	1	Aluminium				
3		Air Inlet Plate	1	Aluminium				
2		Right Side Plate	1	Iron				
1		Motor	1					
序号	代号	名称	数量	材料	单件	总计	备注	
					重量			
		Stage Mark		Material	Ratio	1:1	Weight	
		S		Ningbo Longwell Electric Technology Co., Limited				
		Version A1	Name	Date				
		Design	HE	20251202	LWCD-40190LN-12			
		Audit						
		Technical						
		Standard						
Mark	Qty	Sign	Name	Date	Approve			
					第 1 页	共 1 页		